














## MARBLE CLASSIC COLLECTION

### TECHNICAL SPECIFICATIONS














#### QUALITY LABORATORY

MODEL		MARBLE CLASSIC STATUARIO POLISHED 24X24		
BODY TYPE		PORCELAIN GROUP BIa		
Body Technical Specifications		Test Method	Standard Value	Pass/Fail
	Length and width	ISO 10545-2	± 0.6 %	Yes
	Thickness		± 5 %	Yes
	Straightness of sides		± 0.5 %	Yes
	Surface flatness		± 0.5 %	Yes
	Squareness		± 0.5 %	
	Water absorption	ISO 10545-3	<0.5 %	Yes
	Breaking strength	ISO 10545-4	>1300 N	Yes
	Modulus of rupture		>35 N/mm <sup>2</sup>	Yes
	Frost resistance	ISO 10545-12	RESIST	Yes
	Linear thermal expansion coefficient	ISO 10545-8	9 * 10 <sup>-6</sup> K <sup>-1</sup>	Yes
Surface Technical Specifications		Test Method	Standard Value	Pass/Fail
	Slipperiness	DIN-51130	-	-
		UNE-ENV-12633	CLASS 0	Yes
	Surface abrasion resistance (PEI)	ISO 10545-7	4	Yes
	Deep abrasion resistance	ISO 10545-6	-	-
	Surface hardness (MOHS scale)	EN-101	4	Yes
	Acids and alkalis resistance	ISO 10545-13	GLB/GLB	Yes
	Crazing resistance	ISO 10545-11	RESIST	Yes
	Staining resistance	ISO 10545-14	5	Yes
	Surface Quality	ISO 10545-2	> 95 %	Yes

## MARBLE CLASSIC COLLECTION

### TECHNICAL SPECIFICATIONS

QUALITY LABORATORY

MODEL		MARBLE CLASSIC STATUARIO POLISHED 24X48		
BODY TYPE		PORCELAIN GROUP BIa		
Body Technical Specifications		Test Method	Standard Value	Pass/Fail
	Length and width	ISO 10545-2	± 0.6 %	Yes
	Thickness		± 5 %	Yes
	Straightness of sides		± 0.5 %	Yes
	Surface flatness		± 0.5 %	Yes
	Squareness		± 0.5 %	
	Water absorption	ISO 10545-3	<0.5 %	Yes
	Breaking strength	ISO 10545-4	>1300 N	Yes
	Modulus of rupture		>35 N/mm <sup>2</sup>	Yes
	Frost resistance	ISO 10545-12	RESIST	Yes
	Linear thermal expansion coefficient	ISO 10545-8	9 * 10 <sup>-6</sup> K <sup>-1</sup>	Yes
Surface Technical Specifications		Test Method	Standard Value	Pass/Fail
	Slipperiness	DIN-51130	-	-
		UNE-ENV-12633	CLASS 0	Yes
	Surface abrasion resistance (PEI)	ISO 10545-7	4	Yes
	Deep abrasion resistance	ISO 10545-6	-	-
	Surface hardness (MOHS scale)	EN-101	4	Yes
	Acids and alkalis resistance	ISO 10545-13	GLB/GLB	Yes
	Crazing resistance	ISO 10545-11	RESIST	Yes
	Staining resistance	ISO 10545-14	5	Yes
	Surface Quality	ISO 10545-2	> 95 %	Yes

## MARBLE CLASSIC COLLECTION

### MARBLE CLASSIC SMOKE BROWN POLISHED 24X48

Model: **MARBLE CLASSIC SMOKE BROWN POLISHED 24X48**  
 Reference: **25964 SMOKE BROWN**  
 Size: **60X120** cm  
 Thickness: **11,50** mm  
 Finish: **Ecopulido**  
 Body Type: **PORCELAIN - GROUP BIa**

#### Water absorption

EN ISO-10545-3	Water absorption	< 0,5 %
----------------	------------------	---------

#### Dimensional characteristics

EN ISO-10545-2	Surface quality	> 95%
EN ISO-10545-2	Curvature flatness	± 0,5 % / ± 2,0 mm
EN ISO-10545-2	Thickness	± 5% / ± 0,5 mm
EN ISO-10545-2	Length and Width	± 0,6 % / ± 2,0 mm
EN ISO-10545-2	Rectangularity	± 0,5% / ± 2,0 mm
EN ISO-10545-2	Straightness of sides	± 0,5 % / ± 1,5 mm

#### Mechanical characteristics

EN ISO 10545-11	Cracking resistance	Pass
EN ISO 10545-12	Frost resistance	Pass
EN ISO 10545-9	Thermal shock resistance	Pass
EN ISO-10545-4	Breaking strength	> 1300 N
EN ISO-10545-4	Modulus of rupture	> 35 N/mm <sup>2</sup>

#### Surface characteristics

EN ISO 10545-7	Visible failure at No of revolutions	-
----------------	--------------------------------------	---

#### Chemical characteristics

EN ISO-10545-13	High concentrations of acids and alkalis	GHB/GHB/GHB
EN ISO-10545-13	Low concentrations of acids and alkalis	GLB/GLB/GLB
EN ISO-10545-13	Household chemicals and swimming pool salts	GA/GA
EN ISO-10545-14	Stain resistance	5/-/5/5

## MARBLE CLASSIC COLLECTION

### MARBLE CLASSIC SMOKE BROWN POLISHED 24X48

Model: **MARBLE CLASSIC SMOKE BROWN POLISHED 24X48**  
Reference: **25964 SMOKE BROWN**  
Size: **60X120** cm  
Thickness: **11,50** mm  
Finish: **Ecopulido**  
Body Type: **PORCELAIN - GROUP BIa**

### Non-slip characteristics

ANSI A137	Dynamic coefficient of friction (DCOF)	<b>&lt; 0,42</b>
BS-7976-2	Slip resistance test (PTV) - wet conditions	<b>+16</b>
UNE-ENV-12633	Slip resistance (pendulum test)	<b>0</b>

### CE MARKING



CE Declaration of Performance: **001CPR2017-08-01**

## MARBLE CLASSIC COLLECTION

### MARBLE CLASSIC PLUS POLISHED 30X60

Model: **MARBLE CLASSIC PLUS POLISHED 30X60**  
 Reference: **23463**  
 Size: **75,5X151** cm  
 Thickness: **12,00** mm  
 Finish: **Ecopulido**  
 Body Type: **PORCELAIN - GROUP Bla**

#### Water absorption

EN ISO-10545-3	Water absorption	< 0,5 %
----------------	------------------	---------

#### Dimensional characteristics

EN ISO-10545-2	Surface quality	> 95%
EN ISO-10545-2	Curvature flatness	± 0,5 % / ± 2,0 mm
EN ISO-10545-2	Thickness	± 5% / ± 0,5 mm
EN ISO-10545-2	Length and Width	± 0,6 % / ± 2,0 mm
EN ISO-10545-2	Rectangularity	± 0,5% / ± 2,0 mm
EN ISO-10545-2	Straightness of sides	± 0,5 % / ± 1,5 mm

#### Mechanical characteristics

EN ISO 10545-11	Crazing resistance	Pass
EN ISO 10545-12	Frost resistance	Pass
EN ISO 10545-9	Thermal shock resistance	Pass
EN ISO-10545-4	Breaking strength	> 1300 N
EN ISO-10545-4	Modulus of rupture	> 35 N/mm <sup>2</sup>

#### Surface characteristics

EN ISO 10545-7	Visible failure at No of revolutions	-
----------------	--------------------------------------	---

#### Chemical characteristics

EN ISO-10545-13	High concentrations of acids and alkalis	HB/HB/HB
EN ISO-10545-13	Low concentrations of acids and alkalis	LB/LB/LB
EN ISO-10545-13	Household chemicals and swimming pool salts	A/A
EN ISO-10545-14	Stain resistance	5/-/5/5

## MARBLE CLASSIC COLLECTION

### MARBLE CLASSIC PLUS POLISHED 30X60

Model: **MARBLE CLASSIC PLUS POLISHED 30X60**  
Reference: **23463**  
Size: **75,5X151** cm  
Thickness: **12,00** mm  
Finish: **Ecopulido**  
Body Type: **PORCELAIN - GROUP Bla**

### Non-slip characteristics

ANSI A137	Dynamic coefficient of friction (DCOF)	< 0,42
BS-7976-2	Slip resistance test (PTV) - wet conditions	+16
UNE-ENV-12633	Slip resistance (pendulum test)	0

### CE MARKING



CE Declaration of Performance: **001CPR2017-08-01**

TORONTO  
115 Carnarvon Street  
Toronto, ON M6M 3C9  
T 416 413 9008  
F 416 413 9652

TROY  
1700 Stutz Drive, Ste 92 & 94  
Troy, MI 48084  
T 248 643 6520  
F 248 643 6523

Please note, all specifications have been supplied  
by the manufacturer and are subject to change.

Email: [mail@cercantile.com](mailto:mail@cercantile.com)  
Website: [www.cercantile.com](http://www.cercantile.com)